

Ultra-durable cable assembly

Outstanding protection and reliability

Rugged design

The stainless steel braided jacket of the J9T2AS cable is molded to the 6W connector, ensuring a rugged connection.

Configure this cable assembly for your application with the following model number format (R signifies cable assembly):

R6W-xx-J9T2AS-yy

6W - screw on connector

- 2-pin, MIL-C-5015 style connector compatible with most industrial accelerometers
- IP64-rated to withstand dust and splashed water

xx - Custom second connector

- Order any connector compatible with J9T2AS cable
- Blunt cut option for termination boxes
- Connect to online condition monitoring system
- Go to buy.wilcoxon.com for more cable info

J9T2AS - cable

- Industrial stainless steel overbraid
- Teflon jacketed cable inside with a total diameter of 0.21 inches
- High-temperature twisted pair cable, rated to 200°C
- Kevlar filler for strength
- Braided shield

yy - Order any length

- Standard lengths of 10, 16, 25, 32, 40, 50, 75, 90 and 112 feet
- Build to order lengths available

Harsh environments

A stainless steel braided jacket protects the cable in even the harshest environments, for example:

- Machine tool applications
- Metal shavings are present
- Cable exposed to sharp objects
- Highly abrasive environments

Unbeatable reliability

The 6W to J9T2AS cable assembly from Wilcoxon offers unbeatable reliability at a competitive price.

