

Charge converter

CC701HT

SPECIFICATIONS

TRANSFER CHARACTERISTICS

Sensitivity, $\pm 5\%$		4 mV/pC
Frequency response ¹ :	± 1 dB	2.0 - 10,000 Hz
	-3 dB	1.0 - 20,000 Hz
Nonlinearity		<1%
Harmonic distortion		<1%

INPUT CHARACTERISTICS

Allowable source capacitance, max ²	500 pF
--	--------

OUTPUT CHARACTERISTICS

Output voltage, max	5 V rms
Electrical noise, nominal:	
Source capacitance (transducer + cable)	1,000 pF
Broadband 2.5 Hz to 25 kHz	100 μ V
Spectral 10 Hz	1.41 μ V/ $\sqrt{\text{Hz}}$
100 Hz	0.71 μ V/ $\sqrt{\text{Hz}}$
1,000 Hz	0.63 μ V/ $\sqrt{\text{Hz}}$
10,000 Hz	0.51 μ V/ $\sqrt{\text{Hz}}$

Output impedance (depending on source capacitance)	25 - 150 Ω
--	-------------------

Bias output voltage	12 \pm 2 VDC
---------------------	----------------

POWER REQUIREMENTS

Voltage source	18 - 30 VDC
Constant current ³	2 - 10 mA

ENVIRONMENTAL

Temperature range	-40° to $+100^\circ\text{C}$
-------------------	-------------------------------------

PHYSICAL

Weight	40 grams
Case material	stainless steel

Connectors:


Signal input	Microdot 10-32
Signal output	BNC

- Notes:** ¹ Measured with 500 pF input capacitance.
² For -3 dB point greater than 10 kHz/
³ To minimize the possibility of signal distortion when driving long cables with high vibration signals, 24 to 30 VDC powering is recommended. The higher level constant current source should be used when driving long cables.




Key features

- Designed for use with high temperature, charge mode accelerometers
- Immune to cable motion noise
- Manufactured in ISO 9001 facility



Powering diagram



Note: Due to continuous process improvement, specifications are subject to change without notice. This document is cleared for public release.